

Advantech Panel PCs

Diverse offerings for a wide range of applications

- ✓ Introduction
- ✓ Benefits and Features
- ✓ Selection Guide



ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Advantech's PPC Product Family

Reliable, Cost-Effective, and High-Performance Industrial Panel PCs

Advantech's PPC (panel PC) product family offers highly scalable, economical solutions in a range of performance classes that support various display sizes to satisfy diverse equipment manufacturing and process automation applications. The PPC product portfolio includes an all-in-one series (PPC-3000) and a configurable series (PPC-6000C). The all-in-one series features an optimized design, compact form factor, and industrial-grade specifications, such as rich I/O, flexible expansion slots, and a wide operating temperature range. Regarding the configurable series, these products are designed to be equipped with any mini-ITX motherboard according to price and functionality.

All-in-One Series

Advantech's PPC-3000/3000S series systems are equipped with a fanless, low-power Intel® Core™ i/Atom™ processor. The standard PPC model (PPC-3000 series) features rich I/O and expansion slots that enable system integrators to build complex systems. Meanwhile, the PPC-3000S series systems, which are aimed at industrial IoT applications, are ultra slim devices that feature a stylish appearance to ensure easy integration.

All-in-One

- Fanless
- Compact
- Low power consumption

General Purpose

- Essential I/O
- Ultra slim
- All-metal body

Industry Oriented

- Rich I/O
- Slim
- Expandible
- Wide temperature range

Configurable Series

Compatible with diverse mini-ITX motherboards, the PPC-6000C series allows system integrators to configure the device according to their exact usage requirements. This flexibility and versatility makes PPC-6000C ideal for applications that require high-performance computing and multiple expansions, such as machine vision operations.

Configurable

- Fan
- High computing power
- Selectable motherboard

Customizable

Features




IP65-rated true-flat panel

In addition to IP65 certification for dust and water resistance, Advantech's panel PCs are equipped with a true flat P-CAP/resistive touchscreen, giving the system an elegant and stylish appearance.



Rich industrial-grade I/O

To ensure excellent connectivity for integrating devices and peripherals, Advantech's PPC systems are equipped with multiple industrial-grade I/O, including isolated RS-422/485, GPIO, RS-232, USB 3.0, DisplayPort, and Line Out ports.





PPC-3001S

- 6th gen Intel® Core™ i processor
- PCAP touch screen control
- All-metal body

PPC-3181SW



PPC-3211SW

PPC-3151SW



PPC-3000S

- Intel® Celeron® N4200/N2930/N2807 processor
- PCAP/resistive touch screen control
- All-metal body

PPC-3170

PPC-3170

PPC-3001

- 6/7th gen Intel® Core™ i processor
- PCAP/resistive touch screen control
- PCIe x4/PCI expansion

PPC-3151W



PPC-3151

PPC-3211W

PPC-3000

PPC-3170

- Intel® Atom™ E3845/E3940 processor
- Wide operating temperature (-20 ~ 60 °C/-4 ~ 140 °F)
- Resistive touch screen control
- PCIe x1/PCI expansion

PPC-6000C

- Compatible with diverse mini-ITX MBs
- Supports CPUs with up to 65W TDP
- PCAP/resistive touch screen control
- PCIe x4/2 x PCI or PCIe x1

PPC-6171C



PPC-6191C

PPC-6151C

Expansion slots

PPC series systems feature expansion slots that support a range of optional riser cards, such as PCI, PCIe x1, and PCIe x4, to enable flexible expansion according to the platform specifications.



Wide operating temperature range

All PPC-3000 series systems equipped with an Intel® Atom™ processor support a wide operating temperature range of -20 ~ 60 °C, making them suitable for operation in harsh environments.



Wide input power range

With support for a wide input power range of 12 ~ 24 V_{DC}, Advantech PPC systems can be operated in various industrial environments without necessitating an additional power converter or generating increased energy costs.

Atom



All-metal body

PPC-3000S series products are designed with an all-metal body to ensure an elegant and streamlined appearance.

Accessories



PPC-IPS-AE

A lightweight, intelligent power management module that protects the system from electrical damage and reduces the potential for data losses. This module can serve as a temporary power source during short-term power outages and can ensure safe system shutdowns.



PPC-STAND-A1E

An elegant desktop stand made of aluminum alloy that supports VESA 75/100. This stand allows users to adjust the vertical viewing angle and can be affixed to surfaces using two screws.



PPC-ARM-A03

A swivel arm equipped with a C-clamp to enable installation on any surface. The swivel arm supports 360-degree rotation.



PPC-174T-WL-MTE

A compact wall-mount kit that supports 360-degree rotation and vertical/horizontal viewing angle adjustment.



PPC-WLAN-C1E

An optional WiFi + BT4.2 Combo Module with dual antennae (2T2R) and 802.11 a/b/g/n/ac support.

	PPC-3001S			PPC-3000S						
Model	 PPC-3151SW/3181SW/3211SW			PPC-3060S	PPC-3100S/3120S/3150S/3210SW				 PPC-3150SW/3180SW	
CPU	6th Gen Intel® Core™ i5-6300U			Intel® Celeron® N2807 (1.58 GHz)	Intel® Celeron® N2930 (1.86 GHz)				Intel® Pentium® N4200 (1.1G up to 2.5GHz)	
Memory	1 x SODIMM DDR4 1866/2133 MHz (up to 16 GB)			1 x SODIMM DDR3L 1333 (up to 4 GB)	1 x SODIMM DDR3L, 1333 MHz (up to 8 GB)				1 x SODIMM, DDR3L 1600/1866 (up to 8GB)	
Display Size	15.6"	18.5"	21.5"	6.5"	10.4"	12.1"	15"	21.5"	15.6"	18.5"
Max. Resolution	1920 x 1080	1366 x 768	1920 x 1080	640 x 480	800 x 600	1024 x 768	1024 x 768	1920 x 1080	1366 x 768	1366 x 768
Luminance (cd/m²)	450	450	300	700	400	500	400	300	400	450
Backlight MTBF	50,000	50,000	50,000	50,000	30,000	30,000	50,000	50,000	50,000	50,000
Touchscreen	Multi-touch projected capacitive			5-wire analog resistive				PCT	Multi-touch projected capacitive	
Network (LAN)	2 x GbE (Intel® I211-AT, I219LM)			2 x GbE (Intel® I211)					2 x GbE (Intel® I211)	
I/O	1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 3.0, 2 x USB 2.0, 1 x HDMI, 1 x TPM2.0 (optional module),			1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 2.0, 1 x USB 3.0,					1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 3.0, 2 x USB 2.0, 1 x Line-out, 1 x HDMI,	
Storage	1 x 2.5" SATA bay, 1 x mSATA bay			1 x 2.5" SATA bay (optional), 1 x mSATA bay					1 x 2.5" SATA bay (optional), 1 x mSATA bay	
Expansion Slots	N/A			N/A					N/A	
Additional Expansion	1 x Full-size Mini PCIe			1 x Full-size Mini PCIe					1 x Full-size Mini PCIe	
Input Power	12 ~ 24 V _{DC}			12 ~ 24 V _{DC}					12 ~ 24 V _{DC}	
Operating Temperature	0 ~ 50 °C with SSD			0 ~ 50 °C with SSD					0 ~ 50 °C with SSD	
Operating System	Windows 7/10 (64bit), Linux			Windows 7/10 (64bit), Linux, Android 6.0					Windows 10 (64bit), Linux, Android 8.0	

	PPC-3001				PPC-3000				PPC-6000C			
Model	PPC-3151	 PPC-3151W/3211W	 PPC-3100/3120-RE9A	PPC-3150/3170/3190		 PPC-6121	PPC-6151C	PPC-6171C	PPC-6191C			
CPU	6th Gen Intel® Core™ i5-6300U	7th Gen Intel® Core™ i5-7300U		Intel® Atom™ E3940 (1.6 GHz)		Intel® Atom™ E3845 (1.91 GHz)		8th Gen Intel® Core™ i/ Celeron® processor		Supports processors with up to 65 W TDP depending on the Mini-ITX motherboard		
Memory	1 x SODIMM DDR4, 1866/2133 MHz (up to 16 GB)			1 x SODIMM DDR3L 1600/1866 MHz (up to 8 GB)		1 x SODIMM DDR3L 1333 MHz (up to 8 GB)		2 x 260-pin SO-DIMM DDR4, 2666 MHz (up to 32 GB, 16 GB per SODIMM)		Dependent on the Mini-ITX motherboard specifications		
Display Size	15"	15.6"	21.5"	10.4"	12.1"	15"	17"	19"	12.1"	15"	17"	19"
Max. Resolution	1024 x 768	1920 x 1080	1920 x 1080	800 x 600	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024
Luminance (cd/m²)	400	450	300	400	600	400	350	350	600	400	350	350
Backlight MTBF	50,000	50,000	50,000	30,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000
Touchscreen	Multi-touch projected capacitive			5-wire analog resistive		5-wire analog resistive		5-wire analog resistive		5-wire analog resistive		
Network (LAN)	2 x GbE (Intel® I211-AT, I219LM)			2 x GbE (Intel® I210)		2 x GbE (Intel® I210)		2 x GbE (Intel® I211-AT, I219LM)		Dependent on the Mini-ITX motherboard specifications		
I/O	1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 4 x USB 3.0, 1 x VGA, 1 x DP1.2, 1 x Line-Out, 1 x Mic-In, 1 x TPM2.0 (optional module)			4 x RS-232, 1 x isolated RS-422/485 (by BIOS), 4 x USB 3.0, 1 x Line-out, 1 x Mic-in, 1 x VGA, 1 x HDMI, 1 x GPIO (8 channels, TTL),		1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 1 x USB 3.0, 3 x USB 2.0, 1 x VGA, 1 x DP1.1a, 1 x Line-Out, 1 x Mic-In		4 x RS-232, 1 x isolated RS422/485, 4 x USB3.1, 1 x VGA, 1 x HDMI 1.4 , 1 x Mic in, 1 x Line out, 1 x GPIO (8channels, TTL)		4 x Reserved ports 2 x WLAN antenna ports		
Storage	1 x 2.5"" SATA bay, 1 x M.2 bay (22 x 42 mm)		2 x 2.5" SATA bay, 1 x M.2 bay (22 x 42 mm)	1 x 2.5" SATA bay, 1 x mSATA bay		1 x 2.5" SATA bay, 1 x mSATA bay		1 x 2.5"" SATA bay, 1 x mSATA bay		1 x 2.5" SATA bay, 2 x 2.5" SATA bay (optional)		
Expansion Slots	1 x PCIe x4 or PCI			N/A	(optional) 1 x PCIe x1 or 1 PCI	1 x PCI or 1 x PCIe x1		(optional) 1 x PCIe x4 or 1 x PCI		2 x PCI or 1 x PCIe x 4 (in the accessory box)		
Additional Expansion	1 x Full-size Mini PCIe, (optional) 1 x Cfast,			1 x Full-size Mini PCIe		1 x Full-size Mini PCIe, (optional) 1 x Cfast,		1 x M.2 2230 (E Key)		Dependent on the Mini-ITX motherboard specifications		
Input Power	9 ~ 32 V _{DC}	9 ~ 32 V _{DC}	12 ~ 32 V _{DC}	9 ~ 32 V _{DC}		9 ~ 32 V _{DC}		12 ~ 30 V _{DC}		100 ~ 240 V _{AC} @ 50/60 Hz		
Operating Temperature	0 ~ 50 °C with SSD			-20 ~ 60 °C with SSD		-20 ~ 60 °C with SSD		0 ~ 50 °C with SSD		0 ~ 50 °C with 35W CPU 0 ~ 45 °C with 65W CPU		
Operating System	Windows 7/10 (64bit), Linux	Windows 10 (64bit), Linux		Windows 10 (64bit), Linux, Android 8.0		Windows 7/10(64bit), WEC7, Linux, Android 6.0		Windows 10 (64bit), Linux		Dependent on the Mini-ITX motherboard specifications		

Regional Service & Customization Centers

China	Kunshan 86-512-5777-5666	Taiwan	Taipei 886-2-2792-7818	Netherlands	Eindhoven 31-40-267-7000	Poland	Warsaw 00800-2426-8080	USA	Milpitas, CA 1-408-519-3898
--------------	-----------------------------	---------------	---------------------------	--------------------	-----------------------------	---------------	---------------------------	------------	--------------------------------

Worldwide Offices

Greater China	Asia	Europe	Americas
China	Japan	Netherlands	North America
Toll Free	Toll Free		Toll Free
Beijing	Tokyo	Eindhoven	Cincinnati
Shanghai	Osaka	Breda	Milpitas
Shenzhen	Nagoya		Irvine
Chengdu			Ottawa
Hong Kong			
	Korea	Germany	
	Toll Free	Toll Free	
	Seoul	Munich	
		Düsseldorf	
Taiwan	Singapore	France	Brazil
Toll Free	Singapore	Paris	Toll Free
Taipei & IoT Campus			São Paulo
Taichung			
Kaohsiung			
	Malaysia	Italy	Mexico
	Kuala Lumpur	Milan	Toll Free
	Penang		Mexico City
		UK	
		Newcastle	
		London	
Middle East and Africa	Thailand	Spain	
Israel	Bangkok	Madrid	
	Vietnam	Sweden	
	Hanoi	Stockholm	
	Indonesia	Poland	
	Jakarta	Warsaw	
	Australia	Russia	
	Toll Free	Moscow	
	Melbourne	St. Petersburg	
	India	Czech Republic	
	Bangalore	Ústí nad Orlicí	
	Pune		
		Ireland	
		Galway	