

TX-RX CROSS-REFERENCE

FIBER MEDIA CONVERSION PRODUCTS

DESIGNED FOR ONE-WAY, SECURE DATA APPLICATIONS

COMMON FEATURES

- Plug-and-play, driver-free installation
- Built-in Auto Negotiation and Auto Cross functions

ONE-WAY DATA TRAFFIC MEDIA CONVERTERS										
	Product Family		Giga-MiniMc		MiniMc		McLIM		McPC Giga-MediaLinX Low-Profile PCI	
	Port Configurations		1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber	
	Features		Auto-Cross, Auto-Negotiation		Auto-Cross, Auto-Negotiation		Auto-Cross, Auto-Negotiation, LinkLoss, FiberAlert		Auto-Cross, Auto-Negotiation	
	Device Speed		10/100/1000 Mbps Copper to 1000 Mbps Fiber		10/100 Mbps Copper to 10 Mbps Fiber		10/100 Mbps Copper to 100 Mbps Fiber		10/100/1000 Mbps Copper to 1000 Mbps Fiber	
Distance		Up to 550 m		Up to 80 m		Up to 5 km		Up to 550 m		
Form Factor		Stand-alone / Modular		Stand-alone / Modular		Modular		PCI PC Card		
Dimensions		2.11H x 4.57W x 8.51D cm (0.83H x 1.8W x 3.35D inches)		2.11H x 4.57W x 8.51D cm (0.83H x 1.8W x 3.35D inches)		1.88H x 6.22W x 8.10D cm (0.74H x 2.45W x 3.19D inches)		8.01H x 1.84W x 9.53D cm (3.152H x 0.725W x 3.75D inches)		
Power Options		AC Adapter, IE-PowerTray/18 Dual USB Cable		AC Adapter, USB, IE-PowerTray/18 Single USB Cable		Via 1, 4, 8, 12-Slot Chassis		Through PC Workstation Power Supply		
Model/Part# Description		# 856-10730-TX – also requires # 856-10730-RX TX/SX-MM850-SC		# 855-10622-RX – also requires # 855-10622-RX MM1300-ST		# 855-12622-TX – also requires # 855-12622-RX MM1300-ST		# 855-12920-TX – also requires # 855-12920-RX MM850-SC		