

Advantech Control Cabinet PC

Designed for Machine Construction and
Plant Engineering Applications



- ／ Introduction
- ／ Product Features
- ／ Intelligent Software
- ／ Selection Guide



ADVANTECH

Enabling an Intelligent Planet


www.advantech.com

Advantech Control Cabinet PC

Wide Range of Product Form-factors for Different Mounting Scenarios of Cabinet Applications


Advantech's UNO-1000/3000 series of Embedded Control Cabinet PCs are fanless with high performance, multiple extensions, and ruggedized chassis. With iDoor Technology which supports automation feature extensions such as Fieldbus communication, Wi-Fi/3G, Digital I/O and POE. Versatile Mounting space DIN-Rail Mount, Wall Mount, Enclosure Mount and Panel mount with easy installation indicated market segments. In terms of the type of mounting, with their Control Cabinet PC, they are suitable for IoT gateway, motion and vision applications.

Features & Benefits



Dual Power Input

Dual power input with wide range operating voltage is a fail-safe mechanism to reduce working unit maintaining down time by alternative power input source. And remote power on assists working units go back online from outside of the cabinet.



Dual iDoor Expansion

Advantech's iDoor technology provides simple, flexible, and reliable expansion in high density systems using versatile color identification and multiple functions.



Built-in Digital I/O

Built-in DI/DO for simple I/O control, status detection, lighting control and event triggering in order to save extra cost and devices.



Multiple Expansion

UNO supports latest range of expansion interfaces including PCIe for high density I/O, iDoor for fieldbus modules, PCI for motion cards with easy installation captive thumb screws.



Dual Digital Display

Flexible display options provide resolutions of up to 4K/2K and provide excellent image quality.



Enclosure Mount (UNO-3400)

Compact outside heatsink mounts through a corresponding cut-out in the cabinet or enclosure panel which integrated seals represent high performance as IP67.



IEC-61010 certified

UNO-3382G/ 3384G are evaluated to the UL/ IEC-61010 standard and support book mounting methods which makes them suitable for installing in harsh industrial environments.

UNO-3200 Series



UNO-1000 Series



UNO-3300 Series



UNO-3400 Series



Remote On/Off,
KVM



System
Configuration



Real-time
Response



System
Recovery

Easy Maintenance



Captive Thumb Screw

Operators can work efficiently with captive thumb screws as a superior tool to strengthen swapping HDD, CFAST & PCI/PCland for maintaining storage and expansion devices.



Hot-swap RTC Battery

Removable RTC battery saves time and cost by avoiding disassembling the working unit and shutting down the whole operation.



Hot-swap

Hot-swap HDD deploy software control data each working units v



Intelligent Software

Advantech WebAccess is a 100% web-based SCADA (Supervisory Control And Data Acquisition) software and it acts as an IIoT Platform providing open interfaces for partners to develop IoT applications for different vertical markets. In addition to traditional SCADA functions, WebAccess has an intelligent dashboard, to provide users with cross-platform, cross-browser data analysis and user interface using HTML5 technology. As well as the built-in widgets, WebAccess also provides Widget Builder to allow customers to build their own.

WebAccess/SCADA

WebAccess/HMI

WebAccess/HMI Designer is powerful yet intuitive software to create total solutions for HMI (Human Machine Interface) products. WebAccess/HMI Designer is proven in many application fields and is an easily integrated development tool. WebAccess/HMI Runtime, a part of WebAccess/HMI, guarantees reliability and performance of open platform because of the minimum system overhead, high communication data rates, sub-second screen switching, and 24/7 operation.

Remote Device Management

WISE-Pass/RMM is an innovative remote management and cloud-based software preloaded in all Advantech embedded solutions, allowing the

WISE-PaaS/RMM

efficient and centralized remote monitoring and management of embedded devices in real-time, device health status, system configuration, system protection, and recovery & backup. WISE-Pass/RMM targets the needs of creating a more intelligent and interconnected embedded computing solution.




System Protection

Versatile Mounting with Easy Installation




DIN-Rail Mount

UNO-1000 series can be painlessly installed on the rail with the sophisticated din-rail kit at the rear and R-angle design at the front.



Wall Mount

Easy pull-out operation is extremely convenient that advantage is suitable for all but the heavier installations.



Book Mount

The UNO-3300 offers an open and universal automation solution, saves space and allows quick installation in a control cabinet.



Enclosure Mount

The UNO-3400 series are designed for easier and quick installation in control cabinets. As UNO-3400 which has the Placing-and-Click snap connector which has further considered users' activity and then simplifies the installation procedures.

Expandable Storage

SSD let operators save data or collect data easily when maintaining without interruptions.

Selection Guide



Model Name	UNO-1251G	UNO-1372G-J	UNO-1372G	UNO-1483G	UNO-3272G	UNO-3283G/ 3285G	UNO-3382G/3384G	UNO-3483G
CPU	ARM Coretex A8, 600MHz	Intel® Celeron® J1900 2GHz	Intel® Atom™ E3845 1.91GHz	Intel® Core™ i3-4010U 1.7GHz	Intel® Celeron® J1900	Intel® Core™ i7-6822EQ 2.0GHz Intel® Core™ i5-6442EQ 1.9GHz Intel® Core™ i5-6440EQ 1.9GHz Intel® Core™ i3-6102E 1.9GHz	Intel® Core™ i7-4650U 1.7Hz	Intel® Core™ i7-3612QE
Onboard RAM	256MB DDR2 SDRAM	4GB DDR3L SO-DIMM	4GB DDR3L SO-DIMM	8GB DDR3L SO-DIMM	4GB DDR3L SO-DIMM	8GB DDR4 SO-DIMM	8GB DDR3L SO-DIMM	8GB DDR3L SO-DIMM
Display	-	HDMI, DP	HDMI, VGA	DP, VGA	VGA, HDMI	DVI-I, HDMI	HDMI, DP	VGA, HDMI
Audio	-	-	Line-out	Line-out	Line-out	Mic in, Line out (pin header)	N/A (built-in Line-in/out/Mic,I/O through iDoor)	Mic in, Line out (pin header)
Serial Ports	1 x RS-232, 1x RS-422/485, 1 x RS-485	4 x RS-232/ 422/485	1 x RS-232, 1 x RS-422/485	1 x RS-232, 2 x RS-422/485	2 x RS-232, 2 x RS-232/422/485	2 x RS-232/422/485, 2 x RS-232 (pin header)	1 x RS-232/422/485	1 x RS-232, 1 x RS-422/485 (pin header)
Ethernet Ports	2 x 10/100 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	3 x 10/100/1000 Mbps Base-T	4 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T
USB Ports	1 x USB 2.0	3 x USB 2.0 1 x USB 3.0	2 x USB 2.0 1 x USB 3.0	2 x USB 2.0 2 x USB 3.0	3 x USB 2.0 1 x USB 3.0	6 x USB3.0	2 x USB 2.0 2 x USB 3.0	2 x USB 2.0 2 x USB 3.0
PCIe/PCI Expansion	1 x Mini PCIe	2 x Mini PCIe	2 x Mini PCIe	1 x PCIe x 1 2 x Mini PCIe	2 x PCIe x 1 1 x Mini PCIe	UNO-3283G: 1 x PCIe16+ 1 x PCI, 2 x Mini PCIe UNO-3285G: 2 x PCIe8+ 2 x PCI, 2 Mini PCIe	UNO-3382G: 2 x Mini PCIe UNO-3384G: 2 x MiniPCIe, 1 x PCI + 1 x PCIe x 4	1 x PCIe4, 3 x Mini PCIe
Digital I/O	-	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO (optional)	-	-	-
Micro SD	1 x 1G MicroSD card 1 x MicroSD card slot	-	-	-	-	-	-	-
CFast Slots	-	-	-	-	-	CFast x 1	CFast x 1	-
2.5" HDD Expansion slot	-	1 x SATA HDD	1 x SATA HDD	1 x SATA HDD	1 x SATA HDD	2 x SATA HDD, support RAID 0/1	2 x SATA HDD, support RAID 0/1	2 x SATA HDD, support RAID 0/1
Operating Systems	Windows Embedded Compact7(WEC7), Embedded Linux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8, WES7, AdvLinux
Mounting	DIN-rail Mount	DIN-rail Mount	DIN-rail/Wall Mount	DIN-rail/Wall Mount	Wall, Stand Mount	Wall, Stand, Enclosure Mount	Book Mount	Enclosure Mount
Power Input Range	10-36Vdc	9-36Vdc	10-36Vdc	12/24Vdc ± 20%	10-36Vdc	10-36Vdc	24Vdc ± 20%	12/24Vdc ± 20%
Operating Temperature	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	0 ~ 55°C (32 ~ 131°F)	-20 ~ 60°C (-4 ~ 140°F)
Power Consumption Typical	5.3W	19W	24W	41W	24W	90W	45W	50W
Dimensions (W x D x H)	50 x 90 x 100 mm	65 x 105 x 150mm	85 x 139 x 152 mm	106 x 139 x 198 mm	145 x 177 x 238 mm	UNO-3283G: 142 x 238 x 117 mm UNO-3285G: 182 x 238 x 177 mm	UNO-3382G: 65.2 x 254 x 207mm UNO-3384G: 103.2 x 254 x 207mm	305 x 82 x 225 mm

Advantech iDoor Module

Memory/Storage/External I/O

Communication

FieldBus

Digital / Analog I/O

<p>PCM-2300MR MR4A16B, MRAM, 2MByte</p>	<p>TPM Compliant with TCG 1.2</p>	<p>PCM-23C1CF CFast, Ejection Type I, CFast x 1</p>	<p>PCM-23U1DG Locked USB Slot for USB Dongle, USB x 1</p>
<p>PCM-24D2R2/24D2R4 OXPCle-952 UART, Isolated RS-232, 422/485, DB9 x 2</p>	<p>OXPCle-954 UART, Non-Isolated RS-232, 422/485, DB37 x 1</p>	<p>PCM-24R2PE Intel i350, GbE, PoE IEEE 802.3af, PD, RJ45 x 2</p>	<p>PCM-24R2GL Intel i350 PCIe, GbE, LAN Mini Card, RJ45 x 2</p>
<p>PCM-24R1TP Intel 82574L, GbE, IEEE 1588 PTP, RJ45 x 1</p>	<p>SJA1000 CANBus, CANOpen, DB9 x 2</p>	<p>PCM-24S2WF 802.11 a/b/g/n 2T2R w/ BT4.0, Atheros AR9462, SMA x 2</p>	<p>PCM-24S23G 6-band HSPA Cellular Module, SIM Holder+ GPS, SMA x 2</p>
<p>PCM-24S24G LTE Bands, UMTS/HSPA Bands, GPS/GPRS Bands, SMA x 2</p>	<p>PCM-26D1PB Hilscher netX100 FieldBus, ProfiBus, DB9 x 1</p>	<p>PCM-27D24DI Digital I/O, 16 DI / 8 DO, Isolation, DB37 x 1</p>	

Advantech Innovative Design Concept- Simple, Flexible, Reliable

As a leading provider of Industrial PC, Advantech devoted to innovation product/service development. To be the pioneer in intelligent automation technology, the i-concept represents the intelligent, integrated and intuitive design which covers the innovation of service model, user behavior and cutting-edge technology that opens a new era of industrial automation.



An integrated intelligent key brings simplified intuitive operation for configuring your automation panel. With a flexible software design, customized functions are easier to carry out.



A standardized modular Interface which offers flexible expansion to increase the number of applications and expand system functions through the variety of standardized modular I/Os.



A Reliable Long Distance Transmission Technology which transfers video signals and touch control over a single Ethernet cable which overcomes interference in harsh environments not only for data connections, but also for a cost effective multiple display solution.

Regional Service & Customization Centers

China

Kunshan
86-512-5777-5666

Taiwan

Taipei
886-2-2792-7818

Netherlands

Eindhoven
31-40-267-7000

Poland

Warsaw
48-22-33-23-740 / 41

USA/ Canada

Milpitas, CA
1-408-519-3898

Worldwide Offices

Greater China

China

Toll Free	800-810-0345
Beijing	86-10-6298-4346
Shanghai	86-21-3632-1616
Shenzhen	86-755-8212-4222
Chengdu	86-28-8545-0198
Hong Kong	852-2720-5118

Taiwan

Toll Free	0800-777-111
Neihu	886-2-2792-7818
Xindian	886-2-2218-4567
Taichung	886-4-2378-6250
Kaohsiung	886-7-229-3600

Asia Pacific

Japan

Toll Free	0800-500-1055
Tokyo	81-3-6802-1021
Osaka	81-6-6267-1887

Korea

Toll Free	080-363-9494
Seoul	82-2-3663-9494

Singapore

Singapore	65-6442-1000
-----------	--------------

Malaysia

Toll Free	1800-88-1809
Kuala Lumpur	60-3-7725-4188
Penang	60-4-537-9188

Indonesia

Jakarta	62-21-769-0525
---------	----------------

Thailand

Bangkok	66-2-248-3140
---------	---------------

India

Toll Free	1-800-425-5070
Pune	91-20-39482075
Bangalore	91-80-2545-0206

Australia

Toll Free	1300-308-531
Melbourne	61-3-9797-0100
Sydney	61-2-9476-9300

Europe

Toll Free	00800-2426-8080
Germany	
Munich	49-89-12599-0
Hilden / D'dorf	49-2103-97-885-0

France

Paris	33-1-4119-4666
-------	----------------

Italy

Milano	39-02-9544-961
--------	----------------

Benelux & Nordics

Breda	31-76-5233-100
-------	----------------

UK

Reading	44-0118-929-4540
---------	------------------

Poland

Warsaw	48-22-33-23-740 / 41
--------	----------------------

Russia

Toll Free	8-800-550-01-50
Moscow	7-495-232-1692

Americas

North America

Toll Free	1-888-576-9668
Cincinnati	1-513-742-8895
Milpitas	1-408-519-3898
Irvine	1-949-420-2500

Brazil

Toll Free	0800-770-5355
Saude-São Paulo	55-11-5592-5355

Mexico

Toll Free	1-800-467-2415
Mexico City	52-55-6275-2777

ADVANTECH

Enabling an Intelligent Planet

<http://www.advantech.com>

Please verify specifications before quoting. This guide is intended for reference purposes only. All product specifications are subject to change without notice. No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher. All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2019

More Information



8600000145