



# UPOS-510 Series

## Industrial-Grade Modularized POS System for Diverse Applications



**UPOS-510** is a modern, sleek industrial-grade fanless POS system with IP65-rated front panel protection that features built-in Intel® Celeron® J1900/ Core™-i processor for extreme performance. The modular monitor and peripheral design enables various application supports. The highly expandability I/O design and various secondary display supports can fulfill all type of retail and hospitality applications.



### Stylish, Slim POS System with Modular Design

UPOS-510 is a modern looking, slim and powerful POS system with true-flat design. The 15" modular monitor can also be installed as secondary display and can be a digital signage monitor to fulfill various applications in retail and hospitality.




### Support Various Secondary Display for Improved Purchase Experience

UPOS-510 features a modular design that allows the system to support various types of secondary displays and digital signage devices. It can also be integrated with Advantech's AIM-37 (Serving as the secondary display) for providing additional advertising space to increase potential purchase opportunities.



### Highly Expandable I/O and Superior Data Storage Support

UPOS-510 is equipped with easy-access HDD and USB ports, as well as highly expandable I/O. The system's screw-free rear cover enables easy removal and snap fitting for convenient HDD updates and maintenance. It also incorporates RAID technology to ensure superior storage reliability and database recovery capabilities.



**UPOS-510D** with Intel® Celeron® J1900 processor

**UPOS-510F** with Intel® Core™ i3 / i5 processor



Various Peripherals



IP65-rated Front Panel Protection



「 Power Button 」



USB Connector for Easy Maintenance

		UPOS-510D	UPOS-510F
System	CPU	Intel® Celeron® J1900	Intel® Celeron® 3955U/ Core™ i3-6100U/ Core™ i5-6300U
	Cache Memory	SATA II (3.0Gb/S)	3MB cache memory
	System Memory	SODIMM x 1 (Maximum up to 8GB DDR3L)	SODIMM x 1 (Maximum up to 16GB DDR4-2133)
	Expansion	1 x Full-size mini PCIe (for mSATA/Wi-Fi/BT)	
Storage	HDD	1 x 2.5" SATA HDD/SSD Bay	2 x 2.5" SATA HDD/SSD Bay
	SATA	SATA II (3.0Gb/S)	SATAIII (6.0Gb/S)
Display	Resolution	15" TFT LCD (1024 x 768) with LED backlight	
	Brightness	250 cd/m²	
	Touch Screen	P-Cap Touch (Controller on Touch Board)	
Optional Modules	Serial Port	2 x RS-232 (RJ48 with 5V/12V by internal jumper, 1A selectable)	
	USB Port	1 x USB 2.0, 1x USB 3.0	2 x USB 3.0
	Vedio Output	1 x VGA1 Port (DSUB-15) 1 x Display Port (Reserved for BOX PC)	
	Audio Output	1 x Line-Out & Mic-In	
	Ethernet	1 x RJ-45 Gigabit Ethernet(10/100/1000)	
	Cash Drawer	1 x RJ11 (12V (Default) /24V by internal switch jumper)	
	DC In	60W	90W
	Power Button	Power switch with internal LED indicator	
Optional Modules	Color	15"/ 10.1" TFT LCD (Touch/Non-Touch)	
	Peripherals	<ul style="list-style-type: none"> <li>• MSR</li> <li>• MSR + iButton</li> <li>• MSR + Fingerprint</li> <li>• MSR + RFID</li> </ul>	
	Connectivity	Wi-Fi (802.11 b/g/n), Bluetooth	
Mechanical & Environmental	Color	Black/white/custom	
	Operating Temperature	0 ~ 40° C (32 ~ 104° F)	
	Humidity	10 ~ 95% @ 40° C non-condensing	
	Certifications	CE/FCC/CCC	
Software	OS Support	Win 10, Win 8.1, Win 8, Win 7, POS Ready 7	