

ADVANTECH

Enabling an Intelligent Planet



RYZEN **EPYC**
EMBEDDED EMBEDDED



ADVANTECH AMD SOLUTIONS EBOOK

Your Guide to Advantech's E-IoT Computing Platforms based on the Latest AMD
CPUs Designed Specifically for High Performance Edge Computing

Table of Contents

Advantech In Perspective

Why Advantech?	01
Advantech at a Glance	02
Embedded Design-in Platforms	03
Embedded AIoT Design-in Services	04
Why Advantech & AMD for Embedded	05
How Advantech & AMD Benefit Industrial Applications	06

Edge+ Embedded Solutions

Advantech Product Roadmap	07
Star Products: EPYC™ 7003 Series (SOM-E780, AIMB-592, EPC-B5592)	09
Star Products: Ryzen™ Embedded 5000 Series (AIMB-522, EPC-B3522)	12
Star Products: Ryzen™ Embedded V2000 (SOM-6872, AIMB-229, EPC-T3229)	14
Star Products: Ryzen™ Embedded R2000 (MIO-5376, DPX-S451)	17
Star Products: Ryzen™ Embedded V1000/R1000 (DPX-E265, DPX-E140, DPX-S450, DPX-J100, DS-082)	19
Industrial-grade Peripheral	24
Embedded Software Services	25

Use Cases

Boosting Retail Sales with Digital Advertising Signage	26
Digital Transformation in Medical Imaging Analysis	27
Machine Learning Assisted Computing Upgrade for Automated Visual Inspection Equipment	28
The Regulated Gaming Industry Requires High Performance Hardware with Specialized Hardware and Software Features	29
SOM-E780, Most Powerful COM HPC Module to Enable Fast & Flexible Deployment on 5G Edge AI Server	30
Fastest way to integrate a EV Charging System within a Rugged 3.5" Single Board Computer	31

Product Selection Guide

Advantech Global Presence

32

35

WHY ADVANTECH

Advantech is a leading provider of innovative products, services, and solutions. We offer comprehensive system integration, hardware, software, customer-centric design services, embedded systems, and global logistics support. We work closely with our partners to provide complete solutions for a wide range of applications in different vertical segments.

ADVANTECH



ADVANTECH

Enabling an Intelligent Planet



Est. **1983**

Founder and CEO: **K.C. Liu**
Headquarter: **Taipei, Taiwan**

INDUSTRY SERVED




Telecom, Industry 4.0, IoT, Gaming, Retail, iLogistics, Mil/Aero, Broadcasting, Agriculture, Healthcare
(We work with 27 of the top 30 healthcare companies worldwide)



2000+
STANDARD PRODUCT OFFERINGS

CUSTOM PRODUCT CAPABILITY


72% of what we build is the brand behind the brand for our partners




WORLD'S LARGEST IPC COMPANY

32% market share

● Advantech ● Other IPC Companies



\$2.09B 2021 REVENUE



KEY ECO-SYSTEM PARTNERS



QUALITY SYSTEMS IN PLACE

- OHSAS 81001
- ISO-170256
- IECQ QC 080000
- Sony GP
- IECEx QAR
- FDA

1MILLION+ sq. ft.

In-house manufacturing Kunshan, China, Ten SMT Lines



Linkou, Taiwan



Kunshan, China


MANUFACTURING PLANTS

- Vertically Integrated manufacturing (Self contained)
- Full Manufacturing redundancy (Risk Mitigation)
- Full BOM and lifecycle control (End-to-End control over quality)



\$9.1B MARKET CAP
2022

WORLDWIDE OFFICES



Design Centers	6
Manufacturing Centers	3
CTOS Centers	13
Logistics Centers	4
On-Site Service	2
Repair Centers	14
Sales Offices	19

8500+
EMPLOYEES




Edge⁺ Embedded Design-in Platforms

Rugged & Mission Critical

High Performance Edge Computing

Embedded Vision & Robotics



Embedded AIoT Design-in Services

Embedded Software Services




- Embedded BIOS
- Embedded LTS OS (Long-Term Support OS)
- SUSI Software API and OS Lockdown Utility
- iManager: Intelligent Self-management on Chip

Edge AI




- IE Aggregation for NVIDIA and Intel Accelerators
- Cross-platform Support for Windows and Ubuntu
- Vision AI Turnkey Repository
- Instant AI Experience OOB

Device Management




- Remote Management
- Update Management
- Data Visualization
- Monitor and Control
- Alert and Action
- IT/OT Total Security

Software and Cloud Integration



- Acronis Backup and Recovery
- McAfee IoT Security Solution
- Windows IoT Add on Utility and Customization
- Global Distribution
- Azure Migration and Consulting Services



Why ADVANTCH & AMD for Embedded

Advantech, a leading IPC company, leverages the latest AMD platform technology to deliver superior business value. Accelerating the adoption of IoT edge applications requires technology breakthroughs that support diverse mission critical applications. AMD platform technology provides excellent performance, graphics, embedded features, and design-in services.



5G & Networking

High performance computing for 5G and communication infrastructure

✓ 64-CORE

Machine Vision

Empower precision and expandability to upgrade productivity

✓ 4 PCIe x16



Medical Imaging

Deliver stable computing power for high-definition image analysis

✓ QFCS

Infotainment


AMD Radeon graphics and integration of 4 x 4K independent displays

✓ Radeon GFX




How Advantech & AMD Benefit Industrial Applications

Leading Computing




- AMD Zen 3 architecture
- Advanced 7nm process
- Up to 64 cores
- PCIe Gen 4 and USB 3.2 Gen 2
- Best performance per Watt

Excellent Graphics



- AMD Radeon graphics up to 8 x GPU cores
- 4 x Display pipes up to 4K resolution
- HVEC and H.264 (10-bit) codec, VP9 decode

Software Utility & OS



- DeviceOn / iManager
- Redhat RHEL 8.3
- CentOS 8.3
- Windows Server 2019 & 10 Enterprise LTSC
- Ubuntu 20.04

Embedded Features & Service



- 5 and 10 years Longevity
- BIOS customization services
- Advanced thermal solutions
- Intelligent management (IPMI 2.0)
- Design-in services



Advantech Product Roadmap – Embedded Boards



■ Available ■ Developing

2022 •————• 2023

* All product specifications are subject to change without notice



Advantech Product Roadmap – System Solutions



EPC-T3229 **Q3'22**

- Ryzen™ V2000
- 1U Thin Embedded PC



EBC-B3522 **Q3'22**

- Ryzen™ 5000 (AM4)
- 3U System, 500W PSU



EPC-B5592 **Q3'23**

- EPYC™ 7003 Series
- 4U System, 1200W PSU

Zen 4
Raphael
AM5



DPX®-E140 **Q3'22**

- Ryzen™ V1000/R1000
- Radeon GFX9, 4 x DP out



DPX®-J100 **Q3'22**

- Ryzen™ V1000/R1000
- 72 + 20 Pin JAMMA Harness Connectors



DPX®-S451 **Q4'22**

- Ryzen™ R2000 Zen 2
- Radeon GFX9, 4 DP out



DS-082

- Ryzen™ V1000/R1000
- 4/3 x HDMI 2.0, 1 x LAN, 1 x COM & 4 x USB

Zen +
R2000

■ Available ■ Developing

2022

2023

* All product specifications are subject to change without notice




COM-HPC

SOM-E780

EPYC™ 7003 Series



EMBEDDED



The Most Powerful COM HPC Server Module With 64-Core AMD EPYC CPU

Accelerating the Edge Server Revolution

Learn More



Phase In December 2022

Longevity June 2031

Features

Beyond High-performance COM

- COM-HPC Proprietary Pinout – Size E (200 x 160 mm)
- Proprietary pinout for higher TDP & support for more PCIe
- EYPC 7003 REAL server grade CPU (64C/128T/225W) and socket type CPU

Maximum CPU Cores, High Speed I/O, & RAM

- Single CPU with headroom for the most enterprise workloads
- 512GB large memory size with 4 x DDR4 long DIMM
- 79 x PCIe Gen 4.0 lanes for various add-on cards — NIC, GPU, and FPGA


Cost & Energy Efficient Performance

- Supports more VM per server
- Parallelized cores ideal for NFV & SDN
- High performance-per-watt reduces energy & operation cost

Advanced Network Solution with Security & Service

- Supports IPMB for BMC remote control
- TPM support for advanced security
- Supports security boot or fast boot by customized BIOS

Application



Data Center



High End Test Equipment



Networking



Micro-ATX

AIMB-592

EPYC™ 7003 Series



64-Core AMD EPYC Industrial MicroATX Motherboard

Driving Next-Generation Workloads at Edge

Phase In January 2023

Longevity January 2026

Features

Maximize AI Computing with Latest High-speed Technology

- 4 x PCIe Gen 4.0 x16 slots empower Machine Learning & Deep Learning
- Supporting 2 x double-deck AI-accelerated PCIe x16 card by steel & durable slot
- High-speed PCIe 4.0 onboard SSD by M.2 M-Key connector

Ultimate Performance Powers Workloads at the Edge

- 64 Core AMD Milan EPYC 7003, Zen 3 core 7nm CPU
- Up to 768GB DDR4-3200, 6 x channel memory

High Throughput Connectivity to Cloud

- Dual 10GbE LAN high-bandwidth connectivity empowers big data cloud services
- Dual 1GbE LAN simplifies private cloud deployment

Remote Management

- WISE-DeviceOn features remote access and efficient OTA operations
- IPMI 2.0 centralized management

Application



Precise Diagnostic



Intelligent Video Surveillance



Edge AI & Analytics



4U Edge Computer

EPC-B5592

EPYC™ 7003 Series



Server Grade Edge Computer

For Power-hungry Graphic AI Applications

Phase In March 2023

Longevity January 2026

Features


Superior Computing Power for AI Applications

- AMD EPYC 7003 Milan Server Grade CPU
- 6-channel DDR4 up to 3200MHz for heavy computing workloads
- Dual 10G LAN for smooth data stream
- Integrated with NVIDIA Quadro RTX A6000


Industrial Grade System Design

- ESD protection is designed to sustain IEC Level 4 discharge
- EMC protection is designed for both industrial & residential environments
- 1200W 80+ GOLD power supply to support up to two NVIDIA Quadro GPU cards

Application



PACS Workstation



Surgical Robotics

Hyper-converged Infrastructure - VMmark®3.1.x vSAN



VSI - Login VSITM Pro v4.1.40.1 average



Database - TPC Benchmark™ Express HS



High Performance Computing - ANSYS® LS-DYNA® carss




Integer Performance - SPECrate® 2017_int_base



Micro-ATX

AIMB-522

Ryzen™ Embedded 5000 Series



High Expandability MicroATX Motherboard

Empower the Performance Graphic Computing

Learn More



Features

AMD Zen3 Ryzen™ Embedded 5000 Series Desktop CPU

Supports the latest AMD Ryzen™ Embedded 5000 Series desktop CPU for embedded market applications requiring enterprise reliability. The Instructions Per Clock of the Zen 3 core is 19% higher than Zen 2. In addition, the 2X L3 cache enables faster responsiveness with lower latency. The 8 Cores/16 Threads AMD Zen 3 CPU delivers best-in-class power efficiency with outstanding performance per watt. These features make the Ryzen™ Embedded 5000 a perfect solution for multitasking applications in smart manufacturing, automated visual inspection, and intelligent surveillance.

Made for Camera-based Applications

Four built in Gigabit Ethernet ports and 8 x USB 3.2 10Gbps interfaces deliver connectivity to high data throughput cameras. Customers can integrate more than 10 x high video quality cameras without additional peripherals cards.

Adaptable to Industrial Applications

Supports 1 x PCI-Express x16 Gen4 technology for graphics demanding applications. Furthermore, dual PCI-Express x4 slots offer the expandability to integrate robotic (arm) controller cards for industrial applications. The onboard M.2 M-Key socket supports high-speed SSD for real-time OS operations.

Application



Intelligent Surveillance



Machine Vision



Smart Manufacturing



3U Edge Computer

EPC-B3522

Ryzen™ Embedded 5000 Series



Machine Vision Edge Computer

For AI Applications in Industrial Automation

Phase In September 2022

Longevity January 2026

Features

Desktop Level Computing Platform

- RYZEN™ 9 performance up-to 1.92 x better than Intel Comet lake i9
- RYZEN™ 9 (105W) TDP 17% lower than Alder lake i9 (125W)
- RYZEN™ 9 is 16C/32T for multiple application
- Integrated with NVIDIA Quadro RTX A4500

Industrial Grade System Design

- ESD level 4 (8kV/ 15kV)
- Safety IEC-62368 CB / UL
- Comprehensive EMC protection for both residential and industrial environments

Value-added Software Support

- Windows 10 & Linux Ubuntu Support
- WISE-DeviceOn
- Value-added Software Support

WISE-DeviceOn



Application



Automated Optical Inspection




Visual Inspection AI



COMe Compact

SOM-6872

Ryzen™ Embedded V2000



High Performance 8-Cores COMe Compact Module

Unlock The Hidden Gem For Edge Evolution

Learn More



Phase In November 2021

Longevity January 2026

Features

The Most Powerful COMe Compact Module

- COMe Compact, 8 Core/35 ~ 54W, 6Core/12 ~ 25W SoC
- Scalable with energy efficiency: lower TDP per core
- Up to 64GB dual channel ECC/non-ECC DDR4-3200 RAM
- Support 4 x 4K displays (DP++, HDMI, VGA, LVDS)

BGA SoC with Desktop Performance for Industrial Applications

- 7nm technology with double performance per watt
- 54W low power with desktop 95W level performance
- +40% graphic performance to save the cost on the external graphic card

Application



Ultrasound



Test Equipment




Video Streaming Equipment


Advantech Design-in Service

- No throttling with QFCS compact thermal design @ 60 °C
- iManager + WISE-DeviceOn for easy maintain, device monitoring, I/O control, and remote management
- Ubuntu OS is ready

CPU PassMark



3D Graphics Mark




PerformanceTEST 10.1



Mini-ITX

AIMB-229

Ryzen™ Embedded V2000



THIN Mini-ITX Motherboard

Upgrading Edge Applications with Breakthrough Performance

Learn More



Features

Powerful Computing Empowers Graphics-driven Embedded Devices

Advantech's AIMB-229 increases graphic processing capabilities by 40% using a powerful embedded Radeon™ GPU with up to 7 Cores. It also supports 4 x independent displays with up to 4K60 UHD resolution via 2 x HDMI and 2 x DP++. AIMB-229 provides 6 x USB 3.2 and 1 x PCIe x8 to facilitate high-speed modular add-on cards and diverse peripherals on a compact motherboard designed for medical imaging and machine vision applications.


Slim, Powerful, and Efficient Solution for Mobile Imaging Equipment

AIMB-229 is powered by AMD Ryzen™ Embedded V2000 processors and supports 8-core ZEN 2 CPU cores up to 16 threads. It boasts 64GB DDR4 3200 memory, and M.2 NVMe x4 SSD with 4.2 GHz turbo boost — doubling the computing performance and I/O bandwidth when compared to the previous generation solutions.

Enables Remote Control and Management at the Edge

WISE-DeviceOn provides real-time hardware, software, and peripheral monitoring solutions that deliver real-time alert notifications. It also provides an over-the-air (OTA) BIOS system that facilitates remote BIOS updates and backup recovery mechanisms that prevent unexpected interruptions and boot up failures.

Application



Smart Retail



Gaming



Medical



Embedded PCs

EPC-T3229

Ryzen™ Embedded V2000



1U Slim Edge PC with Expansions

For kiosks that require multi-tasking capacity

Phase In October 2022

Longevity January 2032

Features

Optimal Platform for Slim and Compact Scenarios

- AMD V2718 with 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 SDRAM
- Supporting up to 4 x displays, 2 x DP ports & 2 x HDMI ports
- 1 x M-Key (support 2242/3042/2280), 1 x E-Key (support 2230)

Slim Mechanical Design with Expansion Capabilities

- 1 x Full-height PCIe expansion slot
- Thin design (44.2 mm)
- Compact form factor (330 x 44 x 270 mm)

Application




Interactive KIOSK



Self check-in system


Diagram



3.5" Single Board Computer

MIO-5376

Ryzen™ Embedded R2000



Rugged Single Board Computer

Ultra Fine Display-out and Camera-in for Indoor & Outdoor Applications

Phase In December 2022

Longevity September 2032

Features

For Kiosks, EV Charging Stations, & Passenger Information Systems

- 3 x Simultaneously displays up to 4K@60Hz via HDMI 2.0, DP1.4, and LVDS
- Integrated CANBus for Critical Control Loop in EV charging and Transportations
- High-speed UARTs and I2C cover huge sensor interfaces requirements

Easy High-resolution Camera Connection

- Equips 3 x 2.5GbE with up to 2 x PoE at 100 m distance
- Provides 4 x USB 3.2 with 10Gbps & 5Gbps bandwidth for higher resolution

State-of-the-Art Expansion Ability

- 3 x Simultaneous M.2 expansions for WLAN, WWAN, and storage
- 5G/LTE Capable via M.2 B-key 3052/3042
- High-Speed PCI Express Gen.4 NVMe Storages

Indoor, outdoor, and adopts everywhere

- Support extended temperature operation variants from -40 ~ 85 °C
- Wide-Range Power 12~24V +/- 10% reduce additional size and cost
- IPC-A-610 Class 3 Assembly ensure higher reliability

Application



Access Control System/
Speed Gate



Passenger Information
System



Onboard Information &
Surveillance



Gaming Platform

DPX[®]-S451

Ryzen[™] Embedded R2000



Multimedia Gaming Engine

Highly integrated gaming motherboard features unrivaled performance and PCIe Graphics Expansion

Phase In November 2022

Longevity November 2030

Features

- High-performance AMD Embedded R2000 SOC APUs
- Quad and dual core APUs up to 3.35 (3.7) GHz
- Radeon[™] VEGA GPU with up to 8 x compute units
- Four independent 4k monitors supported
- Comprehensive gaming features
- 12V DC single input or ATX power
- Full featured driver API for I/O and security

Application



Slot Machines



VLTs



GLI compliant

Features



Digital I/O
32/32



Expansion
I²C, PCIe x 16 and
Golden Fingers



DPX[®] Security
suite: Secureboot,
TPM support, DPX[®]
security features, &
BIOS customization



Battery Backed
SRAM
8MB



8 x USB 2.0
3 x USB 3.0



DPX[®]-Software:
Embedded OS, DPX[®]
Diagnostics, & DPX[®]-
Connector DPX[®]-SAS



Displays
4 x DP++ 1.2



10 x COMs: ccTalk,
RS232, ID003,
RS485, TTL, & 3 x
DP++ 1.2



Enclosure
S2000



Graphics Cards
PCIe x 16 Format



M.2, SATA DOM,
HDD, SSD, CFast,
& USB



On-board Micro
Controller PuC



Gaming Platform

DPX[®]-E265

Ryzen[™] Embedded V1000/R1000



Modular Multimedia Gaming Platform

Learn More



Gaming platform allowing custom features and functions to be added for specific markets / applications


Phase In September 2019

Longevity January 2028


Features

- Supports 4 x DP++ 1.2
- Supports PCIe x8 (PCIe x16 connector, Gen 3.0)
- 2 x 260-pin SO-DIMM up to 32 GB DDR4 3200 MHz ECC/Non-ECC SDRAM
- Removable gaming BIOS module for field verification
- Side expansion port for application specific scenarios expansion modules
- Supports 2 x SATA/2 x CFast/1 x M.2
- AMD Ryzen Embedded V1000/R1000 Processors
- Secureboot support

Application



Arcade



Sports Betting



Gaming

Features



Digital I/O
2 x DI



Onboard: 4 x USB
2.0 / 3 x USB 3.1
Via Golden Fingers:
2 x USB 2.0



DPX[®] Security suite:
Secureboot, TPM support,
DPX[®] security features, &
BIOS customization



Displays 4x DP++
v1.2 (3 w R series)



6 x COMs:
ccTalk, RS232,
ID003, RS485, & TTL



DPX[®]-Software:
Embedded OS, DPX[®]
Diagnostics, & DPX[®]-
Connector DPX[®]-SAS



Graphics Cards
PCIe x 16 Format



M.2, SATA DOM,
HDD, SSD, CFast,
& USB



Enclosure
M1000/M2000



Expansion I²C, PCIe
x 16 and Sidebus
modular expansion



On-board Micro
Controller PuCLite



Gaming Platform

DPX[®]-E140

Ryzen[™] Embedded V1000/R1000



Investment Optimized Gaming Platform

Completely integrated system, designed specifically for regulated gaming markets

Learn More



Features

- AMD Ryzen[™] Embedded V1000/R1000 Processors
- High-performance Radeon[™] VEGA series graphics
- 4 x 4k monitor support
- Comprehensive gaming features
- Passive cooling system for up to 25W or 54W with fan cooler
- 12V DC single input or ATX power

Application



Slot Machine



VLTs



GLI Compliant

Phase In January 2019

Longevity January 2028

Features



Digital I/O
32/32



7 x USB 2.0
2 x USB 3.0



DPX[®]-Software:
Embedded OS, DPX[®]
Diagnostics, and DPX[®]-
Connector DPX[®]-SAS



Battery Backed
SRAM 8MB



9 x COMs:
ccTalk, RS232,
ID003, RS485, & TTL



Enclosure Metalwork
Optional



4 x DP++ 1.2
(3 with R series)



M.2, SATA DOM,
HDD, SSD, CFast,
& USB



On-board Micro
Controller PuC



Expansion
I²C



DPX[®] Security suite: Secureboot,
TPM support, DPX[®] security
features, & BIOS customization



Gaming Platform

DPX[®]-S450

Ryzen[™] Embedded V1000/R1000



Features

- AMD Ryzen[™] Embedded V1000/R1000 Processors
- Quad and dual core APUs up to 3.35 (3.8) GHz
- Radeon[™] VEGA GPU with up to 11 compute units
- Four independent 4k monitors supported
- Comprehensive gaming features
- 12V DC single input or ATX power
- Full featured driver API for I/O and security

Application



Slot Machine



VLTs



GLI compliant

Eye Catching Multimedia Powerhouse

Learn More



Highly integrated gaming motherboard features unrivaled performance and PCIe Graphics Expansion

Phase In January 2021

Longevity January 2028

Features



Digital I/O
32/32



Expansion
I²C, PCIe x 16 and
Golden Fingers



DPX[®] Security suite:
Secureboot, TPM support,
DPX[®] security features, &
BIOS customization



Battery backed
SRAM 8MB



8 x USB 2.0
3 x USB 3.0



DPX[®]-Software:
Embedded OS, DPX[®]
Diagnostics, & DPX[®]-
Connector DPX[®]-SAS



Displays
4 x DP++ 1.2
(3 with R Series)



10 x COMs:
ccTalk, RS232,
ID003, RS485, TTL
3 x DP++ 1.2



Enclosure
S2000



Graphics Cards
PCIe x 16 Format



M.2, SATA DOM,
HDD, SSD, & CFAST,
USB



On-board Micro
Controller PuC



Gaming Platform

DPX[®]-J100

Ryzen[™] Embedded V & R Series



Features

- AMD Ryzen[™] Embedded V1000/R1000 Processors
- Quad and dual core APUs
- Radeon[™] VEGA GPU with up to 8 compute units
- Supports up to 3 x independent monitors
- Comprehensive gaming features
- 72 + 20 Pin JAMMA harness connectors
- Optional Enclosure

Application



Street Gaming



Regulated Gaming

JAMMA Gaming Platform

Learn More



A full set of I/O, COMs and security features designed specifically for JAMMA applications and street gaming markets

Phase In February 2022

Longevity January 2029

Features



Digital I/O
24/29



Expansion
I2C & Mini PCI



DPX[®] Security suite
(as below) +iButton



Up to 2MB of
battery backed
FRAM



6 x USB 4 x 2.0 -
2 x 3.1/2.0



DPX[®]-Software:
Embedded OS, DPX[®]
Diagnostics, & DPX[®]-
Connector DPX[®]-SAS



1 x DP++, 1 x HDMI
and 1 x VGA



6 x Coms – RS232/
485 Tx/Rx



Optional Enclosure



ExOnboard audio
amplifier, line out, &
digital SPDIF out I2C



SATA DOM, SSD,
HDD, M.2, USB, &
CFast



On board Micro
Controller



Digital Signage

DS-082

Ryzen™ Embedded V1000/R1000



The Slimmest 4Kx4 Signage Player

For Edge Visualization Solution

Learn More



Phase In February 2022

Longevity January 26

Features

4 x Independent 4K Outputs via HDMI 2.0

Using 4 x independent HDMI 2.0 output enables users to implement 8K TV wall with ease.

Slim Design (only 19 mm)

System design with only 19 mm thickness is presently the world's slimmest signage player

WISE-PaaS/SignageCMS Bundle

Bundled with WISE-PaaS/SignageCMS software, enabling customers to develop their signage system cost effectively and easily.

Application




Kiosks



QSR



Retail (Supermarket)




Industrial-grade Peripherals

SQFlash



- AMD EPYC 7003 Milan Server Grade CPU
- 6-channel DDR4 up to 3200MHz for heavy computing workload
- Dual 10G LAN for smooth data stream

SQRAM



- Comprehensive DRAM series includes pioneer DDR5 and DDR4
- Extended temperature support (-20~ 85 °C /-40 ~ 85 °C)
- Intelligent software for real time monitoring

Industrial Wireless



- Full coverage wireless technology — 5G/Wi-Fi 6/BLE5.2/ LPWA
- Ruggedized industrial solution -40 ~ 85 °C
- Open, agile, certificate-ready wireless kits

Ubuntu Desktop 20.04



- Full-blown graphic UI OS
- Preferred platform for AI, ML, and DL applications
- Consistent OS experience across platforms with long-term support



Embedded Software Services

Embedded Software Services




Windows 10 IoT

ubuntu

yocto
PROJECT

- Embedded BIOS & LTS OS
- SUSI software API & OS lockdown utility
- iManager: Intelligent self-management on chip

Device Management




- Remote management
- Update management
- Data visualization
- Monitor & control
- Alert & action
- IT/OT total security

Edge AI



- Visual AI turnkey repository
- Embedded BIOS & LTS OS
- Instant AI experience OOB
- Cross-platform support for Windows & Ubuntu

Software & Cloud Integration



- Global distribution
- Monitor & control
- Alert & action
- Azure migration & consulting services
- Windows IoT add-on utility & customization



Boosting Retail Sales with Digital Advertising Signage



Intro

Retailers are increasingly using enhanced digital signage in their stores. This customer is a famous health and beauty retailer and pharmacy chain in Europe. They recently added more LCD digital signage systems to their stores in an effort to reduce print & POS requirements, and deliver dynamic content aimed at attracting customers and increasing sales.


Challenges

- Supports multiple simultaneous displays
- Fanless industrial grade design delivers stable long lifespan maintenance
- Slim for easy installation

Solutions and Technologies

- Supports 4 x displays at 4K UHD resolutions
- An ultra-slim profile of just 19 mm with fanless, cable-free design

Diagram



Benefits

- Zero-cost Advantech WISE-PaaS/SignageCMS content management software available
- Slim system design is easily installed into limited space enclosures
- Fanless thermal solution prevents issues caused by dust during long operation periods



Digital Transformation in Medical Imaging Analysis



Intro

Medical imaging systems — such as CT, MRI, X-ray, and ultrasound machines — are important tools for diagnosis prior to intervention. Consequently, imaging analysis accuracy is a matter of life and death.

Challenges

There is a shortage of medical imaging analysis specialists. Indeed, some studies indicate that by 2023, the world will need 31% more specialists than traditional manpower. Medical organizations are expected to fill such jobs. This could result in analysis mistakes, and be exacerbated by shortened working times.

Solutions and Technologies

Graphic AI based edge computers have the potential to tackle this problem. AI algorithms operating with powerful graphics processing capacities can deliver analytic results that help medical professionals diagnose patients accurately faster. The Advantech EPC-B5592 leverages the AMD EPYC 7003 Milan CPU and the NVIDIA Quadro A6000 CPU to deliver server-grade computing power to complex AI tasks.

Diagram



Benefits

- Superior computing power designed for graphic AI applications
- Industrial system design endures harsh EMC environments
- 1200W 80+ GOLD power supply to support up to 2 x NVIDIA Quadro GPU cards



Machine Learning Assisted Computing Upgrade for Automated Visual Inspection Equipment

Intro

Deploying Advanced Visual Inspection solutions in smart manufacturing necessitates high computing power and machine learning capabilities that maximize productivity.


Challenges

Seeking to improve production efficiency, the customer in this case required multiple high-speed digital cameras run with an embedded computer featuring additional machine learning capabilities

Solutions and Technologies

Advantech AIMB-522 and EPC-B3522 leverage high-performance AMD Ryzen Embedded 5000 CPUs with 16 cores. These CPU are capable of managing manufacturing data processing workloads. The high-expandability provided by onboard PCIe x16/x4 slots and the M.2 socket provide the interfaces needed to install add-on cards that engender AI acceleration and/or robot control. In addition, high-speed I/O connectivity with 8 x USB 3.2 Gen 2 (10Gbps) ports and 4 x 1GbE Ethernet ports simplify the adoption of mainstream industrial cameras and help customers build visual inspection machines with ease.

Diagram



Benefits

- Capable of managing multiple high-speed cameras
- Improve manufacturing accuracy and productivity
- Fast deployment and resilience



The Regulated Gaming Industry Requires High Performance Hardware with Specialized Hardware and Software Features



Intro

An OEM slot machine manufacturer was looking for a long term, reliable platform with features that meet the requirements of the Regulated Gaming industry. Their latest gaming content required high-performance hardware.


Challenges

High-performance, long-lifecycle hardware with necessary industry features.

Solutions and Technologies

- DPX-S450 specialized gaming platform
- AMD Ryzen™ Embedded V1000 SOC, Quad core APU at 3.35 GHz (3.8 GHz turbo)
- Integrated Radeon™ “Vega” Graphics Core up to 11 CU (GFX9)
- Supports 4 x independent 4k monitors
- Comprehensive gaming features meet the requirements of GLI-11
- Sophisticated battery backed intrusion logging
- Full featured driver API for I/O and security

Diagram



DPX-S450

Benefits

- Reliable, field-proven platform with track record of regulatory approvals reduces risk and time to market
- High-performance capabilities support the running of up-to-date gaming content on high-resolution screens
- 7 years product lifecycle
- DPX-S450 is the 10th generation of DPX-S and boasts a strong roadmap for upcoming products. This protects customer investment in both hardware and software using cross generational mechanical and API compatibilities



SOM-E780, Most Powerful COM HPC Module to Enable Fast & Flexible Deployment on 5G Edge AI Server

Intro

Edge AI Servers are used in visualized data collection applications. They are often used to monitor, collect, and analyze big data and thus provide valuable business insights and opportunities.


Challenges

Upgrading traditional 13U servers requires too much time and money.

Solutions and Technologies

The Advantech SOM-E780 is equipped with an AMD EPYC 7003 socket CPU with up to 64 cores for superior computing power. It features a 512GB ECC RAM and 79 pairs of PCIe Gen 4.0 within a COM HPC Server module. This reduces edge AI server time to market and corresponding development costs. It is also easily upgraded & maintained, and fulfills a variety of demands in different platforms or 5G server applications. When paired with Advantech's prompt and professional local design in services, it facilitates the rapid exploitation of business opportunities.

Diagram



Benefits

- Featuring a COM-HPC proprietary pinout for EYPC 7003 REAL Server-grade socket CPU, up to 64 Cores to save energy & costs by supporting more VM per server. Producing a solution with high-performance-per-watt
- 79 x PCIe Gen4.0 lanes for various add-on cards, like NIC, GPU, and FPGA
- On-board TPM chipset for Advanced Security
- Active and Passive Thermal Solutions for 60 °C environments



Fastest way to integrate a EV Charging System within a Rugged 3.5" Single Board Computer



Intro

Electric vehicles (EV) and their charging infrastructures are a rapid growth market. Market size is projected reach USD\$ 25.5 billion by 2027. These solutions boast a 26.8% CAGR since 2020.


Challenges

EV charging systems require multiple sub-systems with different control buses according to domain preference. These solutions must connect to watt meters, battery controller logic, external management devices, payment systems, HMI, and displays. Integrating systems with this level of complexity takes time and money.

Solutions and Technologies

The Advantech MIO-5376 is a 3.5" compact single board computer (SBC). It features an AMD 2000 series CPU and provides extraordinary computing and graphics performance, better user experiences, and content displays. MIO-5376 integrates 3 x 2.5GbE ports — including 2 x optional PoE, CANBus, high speed UARTs, and I2C Bus to simplify the integration of power meters, battery controllers, payment systems, HMI, and displays on one board on EV charging stations.

Diagram



Benefits

- AMD R2000 series provides extraordinary computing & graphics capabilities
- Integrated LAN, PoE, CANBus, UARTs, and I2C
- DC-in 12~24V, 0 ~ 60 °C & -40 ~ 85 °C operating temperature





	SOM-E780	AIMB-592	EPC-B5592
	Computer on Module COM-HPC	Industrial Motherboard Micro-ATX	Embedded PC
AMD Processor	EPYC™ 7003 Series	EPYC™ 7003 Series	EPYC™ 7003 Series
Memory	4 x Channel 288-pin DDR4 RDIMM up to 3200MHz, both ECC and Non-ECC supported 4 x RDIMM slots, Max. 512GB (128GB per RDIMM)	6 x Channel 288-pin DDR4 RDIMM up to 3200MHz 6 x DIMM slots, Max. 768GB (128GB per DIMM)	6 x Channel 288-pin DDR4 RDIMM up to 3200MHz 6 x DIMM slots, Max. 768GB (128GB per DIMM)
Display	N/A	VGA	VGA
Expansion	79 x PCIe Gen 4 lanes	4 x PCIe x16 slots	4 x PCIe x16 slots
Power Input	Vin: 11.4-12.6V VSB: 4.75-5.25V	ATX input	ATX input
I/O Ports	1 x 2.5 Gigabit LAN 4x USB 3.2 Gen1 & 4x USB2.0 2 x serial (RS-232) 12 x GPIO 1 x IPMB	2 x 2.5GbE 2 x 10GbE 1 x 1GbE for BMC Management 4 x USB 3.2 Gen1 1 x RS-232	2 x 2.5GbE 2 x 10GbE 2 x 1GbE for BMC Management 4 x USB 3.2 Gen1 1 x RS-232
Thermal (Fan or Fanless)	1U Heatsink 2U Heatsink	CPU cooler	CPU cooler and system fan
Operating Temperature	0 ~ 60 °C	0 ~ 40 °C (Depends on CPU)	0 ~ 40 °C (Depends on CPU)
Dimensions	200 x 160 mm (7.87" x 6.30")	244 x 244 mm	380 x 454 x 176 mm
Software	WISE-DeviceOn Windows Linux	WISE-DeviceOn	WISE-DeviceOn





	AIMB-522	EPC-B3522	SOM-6872	AIMB-229	EPC-T3229	MIO-5376
	Industrial Motherboard Micro-ATX	Embedded PC	Computer on Module COMe Compact	Industrial Motherboard Mini-ITX	Embedded PC	3.5" Single Board Computer
AMD Processor	Ryzen™ Embedded 5000 Series	Ryzen™ Embedded 5000 Series	Ryzen™ Embedded V2000	Ryzen™ Embedded V2000	Ryzen™ Embedded V2000	Ryzen™ Embedded R2000
Memory	4 x Channel 288-pin DDR4 UDIMM up to 3200MHz 4 x DIMM slots, Max. 128GB (32GB per DIMM)	4 x Channel 288-pin DDR4 UDIMM up to 3200MHz 4 x DIMM slots, Max. 128GB (32GB per DIMM)	2-CH 260-pin DDR4, 3200MHz Up to 64 GB (32 GB per SO-DIMM; ECC/non-ECC)	2-CH 260-pin DDR4, 3200MHz Up to 64 GB/ 32 GB per SO-DIMM (ECC/non-ECC)	2-CH 260-pin DDR4, 3200MHz Up to 64 GB/ 32 GB per SO-DIMM (ECC/non-ECC)	2 x channel 260-pin DDR4 SODIMM up to 3200MHz 2 x SODIMM slots, Max. 32GB (16GB per SODIMM)
Display	HDMI, VGA, DP	HDMI, VGA, DP	1 x VGA (optional to DDI) 1 x LVDS (optional to eDP) 2 x DDI	2 x HDMI, 2 x DP (Type-C)	2 x HDMI, 2 x DP (Type-C)	1 x HDMI 2.0b 4K@60 Hz 2 x DP1.4b 4K@60 Hz 1 x LVDS Dual-Channel 18/24-bit WUXGA
Expansion	1 x PCIe x16, 2 x PCIe x4, 1 x M.2 M key & 1 x M.2 E key	1 x PCIe x16, 2 x PCIe x4, 1 x M.2 M key	16 PCIe Gen3 lanes	1 x PCIe x8 1 x M.2 M key & 1 x M.2 E key	1 x PCIe x8 1 x M.2 M key & 1 x M.2 E key	M.2 E-key 2230 M.2 B-key 3052/3042 w/ SIM M.2 M-key 2280 NVMe
Power Input	ATX input	ATX input	Vin: 8.5-20V VSB: 4.75-5.25V	12V DC-in	12V DC-in	DC-in 12-24V +/- 10% AT/ATX Mode
I/O Ports	4 x GbE 8 x External USB 3.2 Gen2 4 x Internal USB 3.0 3 x Internal USB 2.0 2 x Internal RS-232/422/485 4 x Internal RS-232	4 x GbE 8 x External USB 3.2 Gen2	1 x Gigabit LAN 4x USB 3.2 Gen2 & 8x USB2.0 2 x serial (RS-232) 8 x GPIO 1 x HD Audio	2 x GbE 4 x USB Gen 2 2 x USB Type-C 6 x internal RS-232	2 x GbE 4 x USB Gen 2 2x USB Type-C	3 x 2.5GbE (2 PoE Optional) 4 x USB 3.2, 2 x USB 2.0 2 x RS-232/422/485 2 x RS-232 (4-wire) 1 x CAN 2.0 Audio (Line-in/out/MIC) I2C/SMBus Smart Fan Control 1 x SATA Port Inverter Power, HDD Power
Thermal (Fan or Fanless)	CPU Cooler	CPU cooler and system fan	Heat spreader Semi-cooler	CPU cooler	CPU Heat sink and system fan	Fanless for CPU TDP 15W Cooler for CPU TDP 25W
Operating Temperature	0 ~ 40 °C (Depends on CPU)	0 ~ 40 °C (Depends on CPU)	0 ~ 60 °C	0 ~ 60 °C	0 ~ 60 °C (Depends on CPU)	Standard: 0 ~ 60 °C Extended: -40 ~ 85 °C
Dimensions	244 x 244 mm	310 x 360 x 134 mm	95 x 95 mm	170 x 170 mm	330 x 270 x 44 mm	146 x 102 mm
Software	WISE-DeviceOn	WISE-DeviceOn	WISE-DeviceOn Windows Ubuntu 20.04	WISE-DeviceOn	WISE-DeviceOn	Windows 10 IoT Ubuntu 20.04 WISE-DeviceOn





	DPX®-S451	DPX®-E265	DPX®-E140	DPX®-S450	DPX®-J100	DS-082
	Gaming Platform	Gaming Platform	Gaming Platform	Gaming Platform	Gaming Platform	Digital Signage
AMD Processor	Ryzen™ Embedded R2000	Ryzen™ Embedded V1000/R1000	Ryzen™ Embedded V1000/R1000	Ryzen™ Embedded V1000/R1000	Ryzen™ Embedded V & R Series	Ryzen™ Embedded V1000/R1000
Memory	2 x channel 260-pin DDR4 SODIMM up to 3200MHz 2 x SODIMM slots, Max. 32GB (16GB per SODIMM)	2 x channel 260-pin DDR4 SODIMM up to 3200MHz 2 x SODIMM slots, Max. 32GB (16GB per SODIMM)	2 x channel 260-pin DDR4 SODIMM up to 3200MHz 2 x SODIMM slots, Max. 32GB (16GB per SODIMM)	2 x channel 260-pin DDR4 SODIMM up to 3200MHz 2 x SODIMM slots, Max. 32GB (16GB per SODIMM)	2 x Channel DDR4 SODIMM up to 2400MHz	Dual channel DDR4 2400MHz SODIMM
Display	4 x Display Port	4 x Display Port (V1000) 3 x Display Port (R1000)	x4 Display Port (V1000) x3 Display Port (R1000)	4 x Display Port (V1000) 3 x Display Port (R1000)	3 x monitor 1 x DP++ 1 x HDMI 1 x VGA (2 x with R1102)	AMD Radeon HD graphics
Expansion	One PCIe x 16 slot	One PCIe x 16 slot	NA	One PCIe x 16 slot	Half length mini-PCI card	M.2 2230 E Key
Power Input	12VDC and ATX input	12VDC and ATX input	12VDC and ATX input	12VDC and ATX input	AT12V (V1605) 5V/ 12V Jamma 20pins (R series)	19V DC-in (ATX/AT mode)
I/O Ports	2 x Gigabit LAN 11 x USB (8 x USB 2.0, 3 x USB 3.0/2.0) 12 x serial (RS232/CCTalk/TTL/RS485) 2 x I2C ports 1 x Line out 5.1	2 x Gigabit LAN 7 x USB (1 x USB 3.0) 5 x Serial (RS-232/CCTalk/ID003/RS485) 1 x Line out	2 x Gigabit LAN 9 x USB (2x USB 3.0) 11 x serial (RS232/CCTalk/ TTL/RS485) 2 x I2C port 1 x Line out 5.1	2 x Gigabit LAN 11 x USB (8 x USB 2.0, 3 x USB 3.0/2.0) 12 x serial (RS232/CCTalk/TTL/RS485) 2 x I2C ports 1 x Line out 5.1	1 x Gigabit LAN 6 x RS232 4 x USB 2.0 2 x USB 3.1/2.0 1 x Line out 5.1 1 x SPDIF out (Option)	1 x 1Gbe 2 x USB 3.0 2 x USB 2.0 1 x RS-232
Thermal (Fan or Fanless)	Fan	Fan	Fan/Fanless	Fan	Fanless (R1102) Fan (others)	Fanless
Operating Temperature	Board 0 ~ 60 °C System 0 ~ 50 °C	Board 0 ~ 60 °C System 0 ~ 50 °C	Board 0 ~ 60 °C System 0 ~ 50 °C	Board 0 ~ 60 °C System 0 ~ 50 °C	Board 0 ~ 60 °C System 0 ~ 50 °C	0 ~ 40 °C
Dimensions	200 x 170 mm	170 x 185 mm	200 x 270 mm	200 x 170 mm	190 x 190 mm	180 x 190 x 19 mm
Software	DirectPCI API, DPX® Connector SDK, DPX®-SAS Engine	WinPuC serial protocol	DirectPCI API, DPX® Connector SDK, DPX®-SAS Engine	DirectPCI API, DPX® Connector SDK, DPX®-SAS Engine	WinJIOC serial protocol	WISE-DeviceOn




Worldwide Presence

3 Manufacturing Sites

14 Service Centers

4 Logistics Centers

28 Countries



Contact Information

www.advantech.com/contact/inquiryrequestform

